

WS1 Inline Bypass Assembly



Order No. V3478

Clack Corporation introduces a new 1" adapter to use with the WS1 bypass valve. The new adapter will allow the WS1 bypass valve to be used as a stand alone, inline bypass, on any cold water supply.

Injection molded from non corrosive engineering plastic, the WS1 bypass valve is more versatile than other bypass valves available today, because it will accept any of Clack's WS1 valve fitting kits. The WS1 bypass valve, with the new adapter, can be used on any brand of water softener or filter, portable exchange tanks, In/Out filters and even cartridge filter systems.

SPECIFICATIONS:

- **Operating Pressures 20-125 psi / 138-862 kPa**
- **Temperature Ranges 40-110°F / 4-43°C**
- **Install only on cold water supplies**

ASSEMBLIES

ORDER NO.	DESCRIPTION	QTY/CARTON
V3478	WS1 Inline Bypass Assembly 1" Brass Sweat	1
V3478-01	WS1 Inline Bypass Assembly 3/4" Brass Sweat	1

COMPONENT PARTS

ORDER NO.	DESCRIPTION	QTY/CARTON
V3006	WS1 Bypass Assembly	24
V3467	WS1 Bypass Inline Adapter Fittings	24 sets
V3007	WS1 Fitting 1" PVC Male NPT Elbow Assembly	24 sets
V3007-01	WS1 Fitting 3/4" x 1" PVC Solvent Elbow Assembly	24 sets
V3007-02LF	WS1 Fitting 1" Brass Sweat Assembly LF	24 sets
V3007-03LF	WS1 Fitting 3/4" Brass Sweat Assembly LF	24 sets
V3007-04	WS1 Fitting 1" Plastic Male NPT Assembly	24 sets
V3007-05	WS1 Fitting 1.25" Plastic Male NPT Assembly	24 sets
V3007-06	WS1 Fitting 1" Plastic Male BSPT Assembly	24 sets
V3007-07	WS1 Fitting 1.25" & 1.5" PVC Solvent Assembly	24 sets
V3007-08	WS1 Fitting 1.25" Plastic Male BSPT Assembly	24 sets
V3007-09LF	WS1 Fitting 1.25" & 1.5" Brass Sweat Assembly LF	24 sets
V3007-12	3/4" SharkBite® Assembly	24 sets
V3007-13	1" SharkBite® Assembly	24 sets
V3007-14	3/4" Plastic Male BSPT Assembly	24 sets
V3007-15	3/4" John Guest QC Elbow Assembly	24 sets