



Replacement Membrane & Cartridges



T.F.C. Membrane • 50 GPD **Order No. S1229RS**

THIS MEMBRANE IS USED WITH THE FOLLOWING R.O. SYSTEMS:
T.F.C.-335, T.F.C.-435

ORDER NUMBER	DESCRIPTION	OPERATING TEMPERATURE	QUANTITY PER CARTON	CARTON WEIGHT
S1229RS	T.F.C. 50 GPD Reverse Osmosis Membrane	40°F - 100°F 4°C - 38°C	25	16 lbs.



Sediment Cartridge • 5 Micron **Order No. S7011**

THIS CARTRIDGE IS USED WITH THE FOLLOWING R.O. SYSTEM:
T.F.C.-400

ORDER NUMBER	DESCRIPTION	CARTRIDGE STYLE	MAX. REC. FLOW RATE	OPERATING TEMPERATURE	QUANTITY PER CARTON	CARTON WEIGHT
S7011	5 Micron Sediment Cartridge	Radial Flow	1 gpm	40°F - 100°F 4°C - 38°C	24	6 lbs.



Sediment/Carbon Block Cartridge **Order No. S7028**

THIS CARTRIDGE IS USED WITH THE FOLLOWING R.O. SYSTEMS:
T.F.C.-300, T.F.C.-400, T.F.C.-335, T.F.C.-435

ORDER NUMBER	DESCRIPTION	CARTRIDGE STYLE	MAX. REC. FLOW RATE	OPERATING TEMPERATURE	QUANTITY PER CARTON	CARTON WEIGHT
S7028	Sediment/Carbon Block Cartridge	Radial Flow	1 gpm	40°F - 100°F 4°C - 38°C	24	15 lbs.

Replacement Cartridges



Granular Activated Carbon Cartridge Order No. S7025

THIS CARTRIDGE IS USED WITH THE FOLLOWING R.O. SYSTEMS:

T.F.C.-300, T.F.C.-335, T.F.C.-435

ORDER NUMBER	DESCRIPTION	CARTRIDGE STYLE	MAX. REC. FLOW RATE	OPERATING TEMPERATURE	QUANTITY PER CARTON	CARTON WEIGHT
S7025	Granular Activated Carbon Cartridge	Upflow	1 gpm	40°F - 100°F 4°C - 38°C	24	17 lbs.



In Line GAC Post Filter • 2x6 3/8" John Guest Fittings Order No. S7206W-JG

THIS CARTRIDGE IS USED WITH THE FOLLOWING R.O. SYSTEMS:

T.F.C.-400, T.F.C.-435

ORDER NUMBER	DESCRIPTION	MAX. REC. FLOW RATE	OPERATING TEMPERATURE	QUANTITY PER CARTON	CARTON WEIGHT
S7206W-JG	Inline GAC Post Filter	1 gpm	40°F - 100°F 4°C - 38°C	50	21 lbs.

microline[®]

4462 DURAFORM LANE • WINDSOR, WISCONSIN 53598-9716 USA
PHONE (608) 846-3010 FAX (608) 846-2586 SALES/CUSTOMER SERVICE FAX (800) 755-3010