

Clack®



WS1.25CS

WATER SPECIALIST CONTROL VALVE



shown with optional bypass



Certified to NSF/ANSI 44, NSF/ANSI/CAN 61 and 372.

- Solid state microprocessor with easy access front panel settings
- Three modes of operation; meter immediate, meter delayed, or time clock delayed
- Double backwash feature offers optimum regeneration, cleaning ability and efficiency
- 73 selectable pre-programmed regeneration cycles
- Days override feature; 1 – 28 days available
- Backwash and brining ability to 21" diameter tanks
- Downflow regeneration
- Stores system configuration and operation data in nonvolatile memory
- Coin Cell Lithium battery back-up with an 8 hour carry over
- Level VI 15-volt output DC power supply provides safe and easy installation
- Patented one piece expanding seal spacer stack assembly
- Patented linearly reciprocating piston operation
- Control valve design provides optimum service and backwash rates
- Pre or Post treated water regenerant refill
- Reliable and proven DC drive

Water Specialist 1.25" CS Control Specifications

Inlet/Outlet Fittings.....	¾" to 1.5" NPS
Cycles	up to 6
Valve Material	Fiber Reinforced Composite
Regeneration	Downflow

FLOW RATES

Service @ 15 psi drop (includes meter, bypass, and 1.25" fitting kit).....	34 gpm
Backwash @ 25 psi drop	32 gpm (1)
CV Service.....	8.8
CV Backwash.....	6.4

OPERATING PRESSURES

Minimum/Maximum	20 psi - 125 psi
-----------------------	------------------

OPERATING TEMPERATURES

Minimum/Maximum	40° - 110° F
-----------------------	--------------

METER

Accuracy	± 5%
Flow Rate Range.....	0.25 - 34 gpm
Gallon Range.....	20 - 50,000 gallons
Totalizer	1,000 - 9,999,000 gallons

DIMENSIONS & WEIGHT

Distributor Pilot.....	1.32" OD Pipe (1" NPS) or 32 mm OD
Drain Line	¾" or 1" NPT
Brine Line	¾" or ½" OD Poly Tube
Mounting Base.....	2½" - 8 NPSM
Height From Top Of Tank.....	7 ⅝"
Weight	4.5 lbs

ELECTRICAL SPECIFICATIONS

POWER SUPPLY

	<u>U.S.</u>	<u>International</u>
Supply Voltage	100VAC to 120VAC	200VAC to 240VAC
Supply Frequency	50/60 Hz	50/60 Hz
Output Voltage	15VDC	15VDC
Output Current	500 mA	500 mA

TANK APPLICATIONS

Water Softener	6" - 21" Diameter
Water Filter (2)	6" - 24" Diameter

CYCLES OF OPERATION

Cycle	Range of values
1. Backwash 1 st (upflow)	6 - 16
2. Regenerate Draw/Slow Rinse (downflow)	45 - 75
3. Backwash 2 nd (upflow).....	3 - 12
4. Fast Rinse (downflow)	3 - 10
5. Regenerant Refill (in service with treated water).....	As Programmed
6. Service (downflow)	

Options: Backwash Filter, Bypass, Weather Cover

Compatible with the following typical concentrations of regenerants or chemicals: Sodium chloride, potassium chloride, potassium permanganate, sodium bisulfite, chlorine and chloramines

1. Acquired by use of external drain line flow control
2. Filter tank size calculated @ 10 gpm of backwash per square foot of bed area