

Clack® Mineral Tanks



COLORS AVAILABLE:

ALMOND
BLACK
BLUE
GREY
NATURAL

Clack Mineral Tanks are made of high density polyethylene (HDPE) plastic liner with composite fiberglass filament winding over the liner. Clack's design provides a continuous seamless inner liner with a glass filled polypropylene inlet for higher strength and pressure capabilities. Residential and commercial pressure tanks are available from 8" to 35" diameters.

FEATURES:

- For water softener and filtration applications
- Capacities from 6.7 to 189.1 gallons
- 10 year warranty for 8" - 13" vessels
- 5 year warranty for 14" - 35" vessels

MATERIAL OF CONSTRUCTION:

- Inner liner high density polyethylene
- Threaded inlet glass filled polypropylene

OPERATING PARAMETERS:

- Maximum operating pressure: 150 psi
- Maximum operating temperature: 120°F

EXCEEDS NSF/ANSI 44 MINIMUM PERFORMANCE REQUIREMENTS:

- Safety factor: 4:1
- Minimum burst at 600 psi
- Tested to 100,000 cycles/0-150 psi



This product is Tested and Certified by NSF International against NSF/ANSI 44 for material and structural integrity requirements and NSF/ANSI/CAN Standard 61 for material requirements. Certified to NSF/ANSI/CAN 372.

MADE IN THE USA

MINERAL TANK SPECIFICATIONS:

Tank Size (Inches)	Opening Diameter (Inch/mm)	Height with Base (Inch/mm)	Capacity Gallons	Capacity Liters	Capacity Cubic Feet	Empty Tank Weight With Base (Lbs/Kg)	Quantity per Bulk Pack/ Carton
8x35*	2.5/63.5	34.9/886	6.7	25.5	0.90	8.1/3.7	18
8x44	2.5/63.5	44.2/1123	8.6	32.5	1.15	9.8/4.4	18
9x18*	2.5/63.5	18.4/467	3.9	14.8	.52	5.1/2.3	9
9x35*	2.5/63.5	34.8/884	8.2	31.0	1.09	9.5/4.3	16
9x48	2.5/63.5	48.3/1227	11.5	43.7	1.54	12.5/5.7	16
10x18*	2.5/63.5	18.4/468	4.75	18.0	.64	6.3/2.9	8
10x35*	2.5/63.5	35.0/889	10.2	38.8	1.37	10.4/4.7	16
10x40	2.5/63.5	40.6/1031	12.0	45.5	1.61	11.7/5.3	16
10x44	2.5/63.5	44.3/1125	13.2	50.1	1.77	12.4/5.6	16
10x47	2.5/63.5	47.2/1199	14.2	53.8	1.90	13.1/5.9	16
10x54	2.5/63.5	54.4/1382	16.0	60.6	2.14	15.0/6.8	16
12x35*	2.5/63.5	35.4/900	14.60	55.3	1.95	15.4/7.0	9
12x48	2.5/63.5	48.3/1226	21.0	79.6	2.81	18.9/8.6	9
12x52	2.5/63.5	52.8/1341	23	86.6	3.1	19.7/8.9	9
13x54	2.5/63.5	55/1397	28	105.4	3.7	22.5/10.2	9
14x65	2.5/63.5	65.6/1666	39.4	149.2	5.27	37.5/17	1
14x65	4/101.6	65.6/1666	39.4	149.2	5.27	37.5/17	1
16x53	2.5/63.5	54/1371	41.0	155.2	5.48	41/18.6	1
16x65	4/101.6	65.6/1666	51.2	193.8	6.85	42.75/19.4	1
18x65	4/101.6	67.7/1720	73.5	278.1	9.83	52.5/23.8	1
21x62	4/101.6	67.8/1722	89.6	339.1	11.98	75.75/34.4	1
24x72	4/101.6	73.6/1869	120	464.1	16.39	98.25/44.6	1
30x72	4/101.6	72.2/1884	189.1	715.8	25.28	116/52.6	1
30x72	6/152.4	76.0/1930	189.1	715.8	25.28	196/88.9	1
35x72	6/152.4	76.9/1953	227	859.2	30.3	213/96.6	1

*Available with or without base.

Note: All data is for reference only and is subject to change without notice.